

Package: DatastreamR (via r-universe)

September 11, 2024

Title Datastream API

Version 2.0.4

Description Access Datastream content through

<https://product.datastream.com/dswsclient/Docs/Default.aspx>., our historical financial database with over 35 million individual instruments or indicators across all major asset classes, including over 19 million active economic indicators. It features 120 years of data, across 175 countries – the information you need to interpret market trends, economic cycles, and the impact of world events. Data spans bond indices, bonds, commodities, convertibles, credit default swaps, derivatives, economics, energy, equities, equity indices, ESG, estimates, exchange rates, fixed income, funds, fundamentals, interest rates, and investment trusts. Unique content includes I/B/E/S Estimates, Worldscope Fundamentals, point-in-time data, and Reuters Polls. Alongside the content, sit a set of powerful analytical tools for exploring relationships between different asset types, with a library of customizable analytical functions. In-house timeseries can also be uploaded using the package to comingle with Datastream maintained datasets, use with these analytical tools and displayed in Datastream’s flexible charting facilities in Microsoft Office.

License GPL (>= 3)

Encoding UTF-8

Imports httr, jsonlite, logger, ini, stringr, methods

RoxygenNote 7.3.1

Collate 'Common.R' 'DSConnect.R' 'DSRequests.R' 'DSResponse.R'
'DSUserDataObjectBase.R' 'Datastream.R' 'DatastreamR.R'
'DatastreamUserCreated_TimeSeries.R'

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation no

Author LSEG (Datastream) [aut, cre]
Maintainer LSEG (Datastream) <datastreamapi@lseg.com>
Date/Publication 2024-05-13 11:03:16 UTC
Repository https://datastreamapi.r-universe.dev
RemoteUrl https://github.com/cran/DatastreamR
RemoteRef HEAD
RemoteSha 93a8158ad82aad7fbf1b5dd69a3325e5045e6e80

Contents

DataClient	2
DSCConnect	7
DSTimeSeriesCarryIndicator	9
DSTimeSeriesDataInput	10
DSTimeSeriesDateAlignment	11
DSTimeSeriesDateInfo	12
DSTimeSeriesDateRange	13
DSTimeSeriesDateRangeResponse	14
DSTimeSeriesFrequencyConversion	15
DSTimeSeriesRequestObject	16
DSTimeSeriesResponseObject	17
DSTimeSeriesUserObjectBase	18
DSUserObjectAccessRights	20
DSUserObjectBase	20
DSUserObjectFrequency	22
DSUserObjectGetAllResponse	22
DSUserObjectResponse	24
DSUserObjectResponseStatus	25
DSUserObjectShareTypes	25
DSUserObjectTypes	26
TimeSeriesClient	27
Index	34

DataClient

DataClient

Description

An RC class for accessing Datastream content through Datastream Web services API

Value

DataClient object

Super class

`DatastreamR::DSConnect -> DataClient`

Public fields

`useNaNforNotANumber` : TRUE by default. NULLs are replaced to NaN (Not a Number)

Methods**Public methods:**

- `DataClient$new()`
- `DataClient$getData()`
- `DataClient$getDataframe()`
- `DataClient$formatDataRequest()`
- `DataClient$getDataBundle()`
- `DataClient$toDataframe()`
- `DataClient$clone()`

Method `new()`: Initialize method to create Datastream Object

Usage:

```
DataClient$new(
  config = NULL,
  username = "",
  password = "",
  proxys = NULL,
  sslCer = NULL
)
```

Arguments:

`config` : Config path
`username` : Your Id
`password` : Your Password
`proxys` : Proxy details (if any)
`sslCer` : ssl Certificates path

Details: Creates Datastream RC object for accessing Datastream content through Datastream Web Services API

Returns: DataClient object

Examples:

```
\dontrun{
# ds = DataClient$new(NULL, "YourID", "YourPswd")

# OR

# Login using config file
# Config file details provided in DSConnect.R
```

```

ds = DataClient("Config.ini")

# Timeseries requests

df = tryCatch (
  {ds$getData(tickers="VOD", fields=list("PH","PL"),
             start='2022-01-12', end='2022-07-13', kind=1)},
  error = function(e) { stop (message(e))})
print(df)

# Snapshot requests

df = tryCatch (
{ ds$getData(tickers="VOD", fields=list("PH", "PL"),
             start='2022-01-12', kind=0)},
error = function(e) { stop (message(e))})
print(df)
}

```

Method `getData()`: `getData` posts the JSON formatted request and the JSON response is then converted to Dataframe, if `dataToDF` is TRUE.

Usage:

```

DataClient$getData(
  tickers,
  fields = NULL,
  start = "",
  end = "",
  freq = "D",
  kind = 1,
  properties = NULL
)

```

Arguments:

`tickers` : Instruments Eg: "VOD,BARC"
`fields` : Datatypes Eg: list('PH', 'PL', 'PI')
`start` : start date in "YYYY-mm-dd" format Eg: "2019-01-20"
`end` : end date in
`freq` : Refer DSDateFrequencyNames in DSRequests.R
`kind` : 1 - TimeSeries Request (default), 0 - Snapshot Request
`properties` : properties

Returns: Response Class

Method `getDataframe()`: `getDataframe` posts the JSON formatted request and the JSON response is then converted to Dataframe

Usage:

```
DataClient$getDataframe(
  tickers,
  fields = NULL,
  start = "",
  end = "",
  freq = "D",
  kind = 1,
  properties = NULL
)
```

Arguments:

tickers : Instruments Eg: "VOD,BARC"
 fields : Datatypes Eg: list('PH', 'PL', 'PI')
 start : start date in "YYYY-mm-dd" format Eg: "2019-01-20"
 end : end date in
 freq : Refer DSDateFrequencyNames in DSRequests.R
 kind : 1 - TimeSeries Request (default), 0 - Snapshot Request
 properties : properties

Returns: Dataframe

Method formatDataRequest(): This method formats the request provided by client (in form of tickers and fields) to the JSON formatted request.

Usage:

```
DataClient$formatDataRequest(
  tickers,
  fields = NULL,
  start = "",
  end = "",
  freq = "D",
  kind = 1
)
```

Arguments:

tickers : Instruments
 fields : Datatypes
 start : start date
 end : end date
 freq : frequency
 kind : kind = 0 for Snapshot request and Kind = 1 for Timeseries request

Returns: JSON formatted data request

Method getDataBundle(): getData posts the JSON formatted request and the JSON response is then converted to Dataframe, if dataToDF is TRUE.

Usage:

```
DataClient$getDataBundle(dataRequests, properties = NULL)
```

Arguments:

dataRequests : dataRequests should be formed using formatDataRequest method
 properties : properties

Returns: Response Class

Method toDataframe(): Converts the Class response into a Dataframe which can be further used to plot

Usage:

```
DataClient$toDataframe(dataResponse)
```

Arguments:

dataResponse : The raw data response that is ingested into Dataframe

Returns: Dataframe

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
DataClient$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `DataClient$new`
## -----

## Not run:
# ds = DataClient$new(NULL, "YourID", "YourPswd")

# OR

# Login using config file
# Config file details provided in DSConnect.R
ds = DataClient("Config.ini")

# Timeseries requests

df = tryCatch (
  {ds$getData(tickers="VOD", fields=list("PH", "PL"),
    start='2022-01-12', end='2022-07-13', kind=1)},
  error = function(e) { stop (message(e))})
print(df)

# Snapshot requests

df = tryCatch (
  { ds$getData(tickers="VOD", fields=list("PH", "PL"),
    start='2022-01-12', kind=0)},
  error = function(e) { stop (message(e))})
print(df)
```

```
## End(Not run)
```

DSCConnect	<i>initializer</i>
------------	--------------------

Description

initializer

initializer

Public fields

Config : config file path

Username : Your id

Password : Your Password

Proxies : Proxy Server details (if any)

SslCert : ssl Certificates file path

Url : internal parameter set by application

RequestUrl : internal parameter set up by application

Token : Token received on successful logon

TokenExpiry : Expiry time of the token

Timeout : Max Timeout set in Configuration for the process to complete

Version : Application Version

AppID : Application Id

Methods

Public methods:

- [DSCConnect\\$new\(\)](#)
- [DSCConnect\\$getJsonResponse\(\)](#)
- [DSCConnect\\$getToken\(\)](#)
- [DSCConnect\\$isValid\(\)](#)
- [DSCConnect\\$checkToken\(\)](#)
- [DSCConnect\\$clone\(\)](#)

Method new(): DSCConnect connects to the Datastream web service on behalf of derived classes and helps to send and retrieve data

DSCConnect connects to the Datastream web service on behalf of derived classes

Usage:

```

DSConnect$new(
  config = NULL,
  username = NA,
  password = NA,
  proxies = NULL,
  sslCert = NULL,
  service = NULL
)

```

Arguments:

config : config path
 username : your username
 password : your password
 proxies : proxy url, if any
 sslCert : path to ssl cert file
 service : internally set by the application

Details: user details can be supplied from a config file or passed directly as parameters in the constructor of the derived user object type class.

1) Using ini file (e.g. config.ini) with format

```

[credentials]
username=YourID
password=YourPwd

```

```

[proxies]
url=Your Proxy Url
port=Proxy port
username=Proxy Username
password=Proxy Password

```

```

[cert]
sslCertFile=YourCertFile
#only read if no sslCertFile entry
sslCertPath=YourCertPath

```

Method `getJsonResponse()`: This method makes the query against the API service and does some basic error handling

Usage:

```
DSConnect$getJsonResponse(requestUrl, request)
```

Arguments:

requestUrl : Url used to send the Post request
 request : Raw Datastream request

Method `getToken()`: `getToken` uses you credentials to try and obtain a token to be used in subsequent request for data. The returned token is valid for 24 hours

Usage:

DSCconnect\$getToken()

Method IsValid(): IsValid checks whether the token is valid against the token expiry time

Usage:

DSCconnect\$IsValid()

Method CheckToken(): CheckToken checks whether the token is valid against the token expiry time and generates new token if the token has expired.

Usage:

DSCconnect\$CheckToken()

Method clone(): The objects of this class are cloneable with this method.

Usage:

DSCconnect\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

DSTimeSeriesCarryIndicator

DSTimeSeriesCarryIndicator

Description

This list is a supporting attribute for the CarryIndicator properties of the DSTimeSeriesRequestObject and DSTimeSeriesResponseObjects. When you supply data which contains 'Not A Number' values (NaN) to denote non trading days, this list instructs the mainframe in how to store the values.

Usage

DSTimeSeriesCarryIndicator

Format

An object of class list of length 3.

Value

numeric

Fields

Yes Any incoming NaN values are replaced with the last non-NaN value (e.g. 1,2,3,NaN,5,NaN,7,8 will be converted and stored as 1,2,3,3,5,5,7,8).

No Any incoming NaN values are stored as is and returned as NaN values.

Pad This is similar to YES, but also pads the final value for any dates your users may request beyond the last date in your timeseries.

For example, if your timeseries supplies just 3 values 1, NaN and 3, and your user requests a range of dates two days before and two days after your range, your user will receive the following values:

No: NaN, NaN, 1, NaN, 3, NaN, NaN

Yes: NaN, NaN, 1, 1, 3, NaN, NaN

Pad: NaN, NaN, 1, 1, 3, 3, 3

DSTimeSeriesDataInput *DSTimeSeriesDataInput*

Description

This class is a supporting attribute for the DateInput property of the DSTimeSeriesRequestObject. It is used to supply the raw data for the timeseries.

Value

DSTimeSeriesDataInput object

Public fields

StartDate A datetime value defining the start date for the timeseries.

EndDate A datetime value defining the end date for the timeseries.

Frequency The frequency of the timeseries. One of the DSUserObjectFrequency values defined in DSUserDataObjectBase.R

Values An array of float values. Use NULL to represent NotANumber for non-trading days. Alternatively, if you set the DatastreamUserCreated_TimeSeries property useNaNforNotANumber as True, you can use float NaN values.

Methods**Public methods:**

- [DSTimeSeriesDataInput\\$new\(\)](#)
- [DSTimeSeriesDataInput\\$clone\(\)](#)

Method new():

Usage:

```
DSTimeSeriesDataInput$new(
  startDate = NULL,
  endDate = NULL,
  frequency = DSUserObjectFrequency$Daily,
  values = NULL
)
```

Arguments:

startDate A datetime value defining the start date for the timeseries.

endDate A datetime value defining the end date for the timeseries.

frequency The frequency of the timeseries.

values An array of float values

Returns: DSTimeSeriesDataInput object

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
DSTimeSeriesDataInput$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Datastream takes the StartDate, Frequency and Values properties defined here and creates the timeseries based only on these parameters. The EndDate is not actually used internally other than for logging purposes. The true end date is calculated based on the start date, frequency and the supplied list of values. Supply too few or too many values and the mainframe will accept them and set the end date accordingly based on the given frequency for the item.

DSTimeSeriesDateAlignment

DSTimeSeriesDateAlignment

Description

This list is a supporting attribute for the DateAlignment properties of the DSTimeSeriesRequestObject and DSTimeSeriesResponseObjects. When you supply monthly, quarterly or annual data, the dates are stored internally as the first day of the given period and always returned to you through this interface as the first date of the given period. However, when your users request data from Datastream, you can specify whether the dates returned to users are returned with dates set as the start, mid or end of the requested period

Usage

DSTimeSeriesDateAlignment

Format

An object of class list of length 3.

Value

numeric

Fields

EndPeriod This will return dates to your users that represent the last day of the month, quarter or year.

StartPeriod This will return dates to your users that represent the first day of the month, quarter or year.

MidPeriod This will return dates to your users that represent the middle of the month (15th day), quarter (15th of the middle month) or year (30th June).

DSTimeSeriesDateInfo *DSTimeSeriesDateInfo*

Description

This class is a supporting attribute for the DateInfo property of the DSTimeSeriesResponseObject. It describes the basic range of data for the timeseries.

The DateRange property (DSTimeSeriesDateRange described above) of the DSTimeSeriesResponseObject always returns the dates for a given frequency as the first date in each period (e.g. 2022-01-01, 2020-04-01, etc. for quarterly frequencies). However, The StartDate and EndDate values returned in this class for the DSTimeSeriesResponseObject reflect the start and end dates of the range of dates that would be returned to users requesting the data via Datastream For Office, charting, etc. This depends on the DateAlignment property (DSTimeSeriesDateAlignment) of the timeseries. The start and end dates returned here will be either the start, mid or end dates for the set frequency based on the DateAlignment property (see DSTimeSeriesDateAlignment).

Value

DSTimeSeriesDateInfo object

Public fields

StartDate A datetime value defining the start date of the timeseries data

EndDate A datetime value defining the end date for the timeseries.

Frequency The frequency of the timeseries. One of the DSUserObjectFrequency values defined in DSUserDataObjectBase.R

Methods

Public methods:

- [DSTimeSeriesDateInfo\\$new\(\)](#)
- [DSTimeSeriesDateInfo\\$clone\(\)](#)

Method `new()`:

Usage:

```
DSTimeSeriesDateInfo$new(jsonDict)
```

Arguments:

`jsonDict` JSON dictionary (from JSON Response)

Returns: DSTimeSeriesDateInfo object

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
DSTimeSeriesDateInfo$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

DSTimeSeriesDateRange *DSTimeSeriesDateRange*

Description

This class is a supporting attribute for the `DateRange` property of the `DSTimeSeriesResponseObject`. It returns the raw data for the timeseries. The `DateRange` property of the `DSTimeSeriesResponseObject` always returns the dates for a given frequency as the first date in each period. (e.g. 2022-01-01, 2020-04-01, etc. for quarterly frequencies). You specify whether you want your users to receive either the first, mid or end dates in the given period by setting the `DateAlignment` property (`DSTimeSeriesDateAlignment`) of the `DSTimeSeriesRequestObject`.

When you retrieve a list of all your available timeseries using the `GetAllItems` method, since this list could contain many thousand timeseries objects, the `Dates` and `Values` lists will always be `NULL`. Only the `ValuesCount` field will be set to reflect the number of datapoints available for each item. You need to request an individual timeseries (`GetItem` method) in order to receive a response containing actual data in the `Dates` and `Values` properties.

Value

DSTimeSeriesDateRange object

Public fields

- `Dates` • A list of datetime values specifying the dates for each datapoint.
- `Values` • A list of float values specifying the values for each datapoint.
- `ValuesCount` • A count of the number of datapoints in the timeseries.

Methods**Public methods:**

- [DSTimeSeriesDateRange\\$new\(\)](#)
- [DSTimeSeriesDateRange\\$clone\(\)](#)

Method new():*Usage:*

DSTimeSeriesDateRange\$new(jsonDict, convertNullToNans = FALSE)

Arguments:

jsonDict JSON dictionary (from JSON Response)

convertNullToNans FALSE by default, TRUE converts the NULLs in the NaNs (Not a Number)

Returns: DSTimeSeriesDateRange object**Method clone():** The objects of this class are cloneable with this method.*Usage:*

DSTimeSeriesDateRange\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

DSTimeSeriesDateRangeResponse*DSTimeSeriesDateRangeResponse*

Description

DSTimeSeriesDateRangeResponse is the object returned from the timeseries GetTimeseriesDateRange method. This method allows you to determine the supported dates between given start and end dates at a specified frequency.

Value

DSTimeSeriesDateRangeResponse object

Public fields

Dates A list of datetime values representing the supported dates between requested start and end dates at a specified frequency.

ResponseStatus This property will contain a DSUserObjectResponseStatus value. DSUserObjectResponseStatus\$UserObjectSuccess represents a successful response.

ErrorMessage If ResponseStatus is not DSUserObjectResponseStatus\$UserObjectSuccess this status string will provide a description of the error condition.

Properties Not currently used and will currently always return NULL.

Methods

Public methods:

- [DSTimeSeriesDateRangeResponse\\$new\(\)](#)
- [DSTimeSeriesDateRangeResponse\\$clone\(\)](#)

Method new():

Usage:

```
DSTimeSeriesDateRangeResponse$new(jsonDict = NULL)
```

Arguments:

jsonDict : JSON dictionary (from JSON Response)

Returns: DSTimeSeriesDateRangeResponse object

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
DSTimeSeriesDateRangeResponse$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

DSTimeSeriesFrequencyConversion

DSTimeSeriesFrequencyConversion

Description

This list is a supporting attribute for the FrequencyConversion properties of the DSTimeSeriesRequestObject and DSTimeSeriesResponseObjects. This enumeration specifies how to return values if your end users requests the timeseries at a lower frequency. For example: if your timeseries has daily frequency data, and your user requests monthly or quarterly data, the FrequencyConversion property instructs the mainframe how to return monthly or quarterly data.

Usage

```
DSTimeSeriesFrequencyConversion
```

Format

An object of class list of length 4.

Value

numeric

Fields

EndValue The daily value for the end of the requested period will be returned.

AverageValue The average of all the values for the requested period will be returned.

SumValues The sum of all the values for the requested period will be returned.

ActualValue The actual value for the requested start date will be returned for the same given date in the requested period.

DSTimeSeriesRequestObject

DSTimeSeriesRequestObject

Description

This is a subclass of DSTimeSeriesUserObjectBase and is used to create or modify a timeseries. (See DSTimeSeriesUserObjectBase for details of all the superclass properties.)

Value

DSTimeSeriesRequestObject object

Super classes

[DatastreamR::DSUserObjectBase](#) -> [DatastreamR::DSTimeSeriesUserObjectBase](#) -> DSTimeSeriesRequestObject

Public fields

Id A valid TimeSeries Id

DataInput A DSTimeSeriesDataInput object used to supply the start date, end date, frequency and list of data values. (See DSTimeSeriesDataInput for details.)

Methods**Public methods:**

- [DSTimeSeriesRequestObject\\$new\(\)](#)
- [DSTimeSeriesRequestObject\\$clone\(\)](#)

Method new():

Usage:

```
DSTimeSeriesRequestObject$new(
  id = "",
  startDate = NULL,
  endDate = NULL,
  frequency = NULL,
  values = NULL
)
```

Arguments:

id A valid TimeSeries Id
 startDate A datetime value defining the start date for the timeseries
 endDate A datetime value defining the end date for the timeseries
 frequency The frequency of the timeseries. DSUserObjectFrequency is defined in DSUser-DataObjectBase.R
 values list of float values

Returns: DSTimeSeriesRequestObject object

Method clone(): The objects of this class are cloneable with this method.

Usage:

DSTimeSeriesRequestObject\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

DSTimeSeriesResponseObject

DSTimeSeriesResponseObject

Description

This is a subclass of DSTimeSeriesUserObjectBase and is used to return the details for a timeseries. (See DSTimeSeriesUserObjectBase for details of all the superclass properties.)

Value

DSTimeSeriesResponseObject object

Super classes

[DatastreamR::DSUserObjectBase](#) -> [DatastreamR::DSTimeSeriesUserObjectBase](#) -> DSTimeSeriesResponseObject

Public fields

DateInfo A DSTimeSeriesDateInfo object defining the start date, end date and frequency of the timeseries.

DateRange A DSTimeSeriesDateRange object used to return the dates and values stored in the timeseries. See DSTimeSeriesDateRange for details.

Methods**Public methods:**

- [DSTimeSeriesResponseObject\\$new\(\)](#)
- [DSTimeSeriesResponseObject\\$clone\(\)](#)

Method new():*Usage:*

DSTimeSeriesResponseObject\$new(jsonDict = NULL, convertNullToNans = FALSE)

Arguments:

jsonDict : JSON dictionary (from JSON Response)

convertNullToNans : FALSE by default, TRUE converts the NULLs in the NaNs (Not a Number)

Returns: DSTimeSeriesResponseObject object**Method clone():** The objects of this class are cloneable with this method.*Usage:*

DSTimeSeriesResponseObject\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

DSTimeSeriesUserObjectBase*DSTimeSeriesUserObjectBase*

Description

This is the base object for creating or requesting timeseries data. It has two subclasses DSTimeSeriesRequestObject and DSTimeSeriesResponseObject. It defines the basic attributes for a timeseries. It subclasses DSUserObjectBase which defines the basic attributes common to all five user created item types supported by the API.

Specifics of some of the properties of the DSUserObjectBase superclass

ID

The ID property is defined in DSUserObjectBase but has a specific format for timeseries. Timeseries IDs must be 8 alphanumeric characters long, start with TS followed by 6 uppercase alphanumeric characters. For example: TSTEST01, TS123456, TSMYTEST, etc.

Mnemonic

The Mnemonic property is defined in DSUserObjectBase but should always be left empty or set the same as the ID property for timeseries requests. As a safety measure, this class always ensures it's the same as the ID. In a response from the API server, the value will always be the same as the ID. (see DSUserObjectBase for a description of the other properties)

DSTimeSeriesUserObjectBase specific properties

Value

DSTimeSeriesUserObjectBase object

Super class

[DatastreamR::DSUserObjectBase](#) -> DSTimeSeriesUserObjectBase

Public fields

ManagementGroup This is an optional group name that allows you to organise timeseries into distinct 'folders' displayed in the search category of Navigator. This can be up to 10 uppercase alphanumeric characters. Leave blank for the item to be assigned under the 'GENERAL' group.

Units This is a optional qualifying unit for your data. For example: tons, US\$ millions, index, etc. Maximum 12 characters.

DecimalPlaces A numeric value between 0 and 8 decimal places specifying how many decimal places to use when storing data. The maximum length including decimals for a value is 10 characters including the decimal point. Boundary case examples are 0.12345678, 1234567890, 123456789.0, etc.

FrequencyConversion A DSTimeSeriesFrequencyConversion enum value specifying how to return values if a user requests data at a lower frequency than the timeseries data is supplied. See DSTimeSeriesFrequencyConversion for details.

DateAlignment A DSTimeSeriesDateAlignment enum value specifying whether dates for certain frequencies should be returned as the start, middle or end date of the period. See DSTimeSeriesDateAlignment for details.

CarryIndicator A DSTimeSeriesCarryIndicator enum value specifying how to treat 'Not A Number' values for non-trading days and how to represent values if users request data after the end of the timeseries range. See DSTimeSeriesCarryIndicator for details.

PrimeCurrencyCode An optional 2 character currency code for your timeseries.

HasPadding This property has been replaced with the CarryIndicator property and will always be False

UnderCurrencyCode This property has been deprecated and will always return NULL

AsPercentage This This property has been deprecated and will always return False

Methods**Public methods:**

- [DSTimeSeriesUserObjectBase\\$new\(\)](#)
- [DSTimeSeriesUserObjectBase\\$clone\(\)](#)

Method new():

Usage:

DSTimeSeriesUserObjectBase\$new(jsonDict)

Arguments:

jsonDict JSON dictionary (from JSON Response)

Returns: DSTimeSeriesUserObjectBase object

Method clone(): The objects of this class are cloneable with this method.

Usage:

DSTimeSeriesUserObjectBase\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

DSUserObjectAccessRights

Datastream User Object access rights

Description

All user created objects have a flag specifying if they can be modified by the u All items that have their ShareType property set to DSUserObjectShareTypes. PrivateUserGroup will also have their AccessRight property set to ReadWrite. Global expression objects, not being editable by users, will have the AccessRight property set to Read.

Usage

DSUserObjectAccessRights

Format

An object of class list of length 2.

Value

numeric

DSUserObjectBase

DSUserObjectBase

Description

DSUserObjectBase is the base object for all five user object types. It defines the properties common to all the types

Value

DSUserObjectBase object

Public fields

- Id** The object identifier. The format is specific to each object type. See the individual object file for the particular specification
- Mnemonic** For all object types bar indices, this is the same as the Id property. For indices, the ID (of the form X#:Xnnnnn where n is a digit) is returned when you create an index and is used to manage the index via the API interface. The Mnemonic property is specified when creating an index and is used to reference the index when using Datastream tools such as Charting, Datastream For Office, etc. A mnemonic has format X#aaaaa where aaaaa is 1 to 6 alphanumeric characters.
- DisplayName** A string describing the object. The maximum length varies from object type to object type.
 Expression: Max 30 alphanumeric characters.
 Index: Max 60 alphanumeric characters.
 List: Max 60 alphanumeric characters.
 Regression: Max 50 alphanumeric characters.
 Timeseries: Max 64 alphanumeric characters.
- Description** Currently this isn't supported. When the API returns an object, the Description property will be the same as the DisplayName property.
- Created** a datetime value representing the date when the object was first created.
- LastModified** a datetime value representing the date when the object was last updated.
- Owner** The parent Datastream ID that owns the object. This will be the parent of your Datastream ID. For global expressions this will always be 'Admin'
- ShareType** For all objects except global expressions, this will be DSUserObjectShareTypes.PrivateUserGroup. For global expressions it will be DSUserObjectShareTypes.Global.
- AccessRight** For all objects except global expressions, this will be DSUserObjectAccessRights.ReadWrite. For global expressions it will be DSUserObjectAccessRights.Read.

Methods**Public methods:**

- [DSUserObjectBase\\$new\(\)](#)
- [DSUserObjectBase\\$SetSafeUpdateParams\(\)](#)
- [DSUserObjectBase\\$clone\(\)](#)

Method new(): Initialize*Usage:*

DSUserObjectBase\$new(jsonResp = NULL)

Arguments:

jsonResp : json Response

Returns: DSUserObjectBase object

Method SetSafeUpdateParams(): The following parameters are set only in response when we query for user created items. This method is called before Create or Update to ensure safe values set prior to JSON encoding

Usage:

DSUserObjectBase\$SetSafeUpdateParams()

Returns: No return value

Method clone(): The objects of this class are cloneable with this method.

Usage:

DSUserObjectBase\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

DSUserObjectFrequency *DSUserObjectFrequency*

Description

Regressions and Timeseries objects specify a frequency for the underlying data. DSUserObjectFrequency defines the supported frequencies.

Usage

DSUserObjectFrequency

Format

An object of class list of length 5.

Value

numeric

DSUserObjectGetAllResponse
DSUserObjectGetAllResponse

Description

This is the object returned for the client class' GetAllItems query only.

For GetAllItems queries only, the returned objects will not have all their property fields set. Specifically for below:

Expression: All property fields are fully populated.

Index: The ConstituentsCount property will correctly specify the number of constituents but the Constituents property will be NULL.

List: The ConstituentsCount property will correctly specify the number of constituents but the Constituents property will be NULL.

Regression: All property fields are fully populated.

Timeseries: The ValuesCount field of the DateRange property will specify the number of date value pairs, but the Dates and Values fields will be NULL.

You need to query for the individual object using the GetItem request to retrieve the full content for the object.

Value

DSUserObjectGetAllResponse object

Public fields

UserObjectType specifies the returned object types. e.g. DSUserObjectTypes.List, DSUserObjectTypes.TimeSeries, etc.

UserObjects An array of the specified object types such as DSListUserObject, DSRegressionUserObject, etc.

UserObjectsCount The number of objects returned in the UserObjects property.

ResponseStatus This property will contain a DSUserObjectResponseStatus value. DSUserObjectResponseStatus.UserObjectSuccess represents a successful response.

ErrorMessage If ResponseStatus is not DSUserObjectResponseStatus.UserObjectSuccess this status string will provide a description of the error condition.

Properties Not currently used and will currently always return NULL.

Methods

Public methods:

- [DSUserObjectGetAllResponse\\$new\(\)](#)
- [DSUserObjectGetAllResponse\\$clone\(\)](#)

Method new(): Initialize

Usage:

```
DSUserObjectGetAllResponse$new(jsonResp = NULL)
```

Arguments:

jsonResp JSON Response

Returns: DSUserObjectGetAllResponse object

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
DSUserObjectGetAllResponse$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

DSUserObjectResponse *DSUserObjectResponse*

Description

This is the object returned from the client class' GetItem, CreateItem, UpdateItem and DeleteItem requests.

Value

DSUserObjectResponse object

Public fields

UserObjectId The ID of the object requested. If the item is deleted, the UserObject property will be NULL but the UserObjectId field will be populated

UserObjectType specifies the returned object type. e.g. DSUserObjectTypes.List, DSUserObjectTypes.TimeSeries, etc.

UserObject For all queries bar DeletItem, if the query is successful, this property will contain the user created item requested.

ResponseStatus This property will contain a DSUserObjectResponseStatus value. DSUserObjectResponseStatus.UserObjectSuccess represents a successful response.

ErrorMessage If ResponseStatus is not DSUserObjectResponseStatus.UserObjectSuccess this status string will provide a description of the error condition.

Properties Not currently used and will currently always return NULL.

Methods

Public methods:

- [DSUserObjectResponse\\$new\(\)](#)
- [DSUserObjectResponse\\$clone\(\)](#)

Method new(): Initialize

Usage:

DSUserObjectResponse\$new(jsonResp = NULL)

Arguments:

jsonResp JSON Response

Returns: DSUserObjectResponse object

Method clone(): The objects of this class are cloneable with this method.

Usage:

DSUserObjectResponse\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

DSUserObjectResponseStatus

DSUserObjectResponseStatus

Description

All client methods to retrieve or modify user created items return a response object which includes a ResponseStatus property. The ResponseStatus property specifies success or failure for the request using a DSUserObjectResponseStatus value

Response Values:

UserObjectSuccess : The request succeeded and the response object's UserObject(s) property should contain the (updated) object (except for DeleteItem method).

UserObjectPermissions : Users need to be specifically permissioned to create custom objects. This flag is set if you are not currently permissioned.

UserObjectNotPresent : Returned if the requested ID does not exist.

UserObjectFormatError : Returned if your request object is not in the correct format.

UserObjectTypeError : Returned if your supplied object is not the same as the type specified.

UserObjectError : The generic error flag. This will be set for any error not specified above.

Examples are:

1. Requested object ID is not present

2. You have exceeded the number of custom objects permitted on your account.

Usage

DSUserObjectResponseStatus

Format

An object of class list of length 6.

Value

numeric

DSUserObjectShareTypes

DSUserObjectShareTypes

Description

All user created objects have a flag specifying how they are shared with other users. Currently only PrivateUserGroup and Global are supported.

PrivateUserGroup are items created by any Datastream ID that shares a parent Datastream ID with your ID. Only children of the parent ID can access the user o Expressions can be either PrivateUserGroup or Global. Like the other object types, PrivateUserGroup items are items created by users and visible to just children of their Datastream parent ID. PrivateUserGroup expressions have the ID signature Eaaa, where 'a' is any alphabetical character.

Global expressions are Datastream owned expressions that are available for use by any client. These have the signature nnnE, where n is a digit. Global expressions can be retrieved using the API service, but you cannot modify them. Only your PrivateUserGroup items can be modified.

Usage

DSUserObjectShareTypes

Format

An object of class list of length 5.

Value

numeric

DSUserObjectTypes	<i>DSUserObjectTypes</i>
-------------------	--------------------------

Description

Five user created types are supported. When the client classes communicate with the API server, a DSUserObjectTypes property is set to specify the object type. Responses from the API server also specify the type of the object being returned.

Usage

DSUserObjectTypes

Format

An object of class list of length 6.

Value

numeric

TimeSeriesClient	<i>TimeSeriesClient</i>
------------------	-------------------------

Description

This is the client class that manages the connection to the API server on your behalf. It allows you to query for all your timeseries and to create/modify new timeseries.

Details

Methods Supported

`GetAllItems` : Allows you to query for all the current timeseries available for your use.

`GetItem` : Allows you to download the details of a specific timeseries item.

`GetTimeseriesDateRange` : Allows you to determine the supported timeseries dates between supplied start and end dates at a specified frequency.

`CreateItem` : Allows you to create a new timeseries item with up to 130 years of daily data.

`UpdateItem` : Allows you to update an existing timeseries.

`DeleteItem` : Allows you to delete an existing timeseries.

Value

TimeSeriesClient object

Super class

`DatastreamR::DSConnect` -> TimeSeriesClient

Public fields

`useNaNforNotANumber` If Enabled, NaN is appears in output response instead of NULL

`TimeseriesResponseType` Response type

Methods

Public methods:

- `TimeSeriesClient$new()`
- `TimeSeriesClient$.checkValidTimeseriesId()`
- `TimeSeriesClient$.checkTimeSeriesReqValidity()`
- `TimeSeriesClient$.checkKeyTimeseriesProperties()`
- `TimeSeriesClient$.asGetAllResponse()`
- `TimeSeriesClient$.asGetResponse()`
- `TimeSeriesClient$.jsonRequestEncoder()`
- `TimeSeriesClient$.jsonResponseDecoder()`
- `TimeSeriesClient$GetAllItems()`
- `TimeSeriesClient$GetItem()`

- [TimeSeriesClient\\$CreateItem\(\)](#)
- [TimeSeriesClient\\$updateItem\(\)](#)
- [TimeSeriesClient\\$DeleteItem\(\)](#)
- [TimeSeriesClient\\$getTimeseriesDateRange\(\)](#)
- [TimeSeriesClient\\$clone\(\)](#)

Method new(): User details can be supplied from a config file or passed directly as parameters in the constructor of the derived user object type class. (See the DSConnect superclass for a description of the connection parameters required)

Usage:

```
TimeSeriesClient$new(
  config = NULL,
  username = NULL,
  password = NULL,
  proxies = NULL,
  sslCer = NULL
)
```

Arguments:

config Configuration File path
 username Your Datastream Id
 password Your Password
 proxies Proxies if any
 sslCer Path to CA bundle certificates file

Details: Timeseries Properties:

useNaNforNotANumber : Non-trading days are stored as double NaNs on Datastream, JSON protocol permits NaNs as valid numbers. Thus, all the NULLs in the converted to NaNs in the JSON requests. Responses contain the NULLs, But this should be converted to Nans for Plotting purposes. If you want to receive NaN float values, set useNaNforNotANumber to TRUE, any NULLs in the returned array of float values will be converted to NaNs.

Returns: TimeSeriesClient object

Method .checkValidTimeseriesId(): A helper method to check the timeseries Id

Usage:

```
TimeSeriesClient$.checkValidTimeseriesId(inputId)
```

Arguments:

inputId : Timeseries Id

Returns: NULL if Timeseries id is valid else error string

Method .checkTimeSeriesReqValidity(): A helper method to check some of the mandatory fields of timeseries for its validity

Usage:

```
TimeSeriesClient$.checkTimeSeriesReqValidity(tsItem)
```

Arguments:

tsItem Timeseries Item

Returns: NULL if Timeseries id is valid else error string

Method .checkKeyTimeseriesProperties(): A helper method to check the Timeseries properties

Usage:

TimeSeriesClient\$.checkKeyTimeseriesProperties(tsItem)

Arguments:

tsItem Timeseries Item

Returns: NULL if Timeseries id is valid else error string

Method .asGetAllResponse(): A helper method which converts the JSON response to GetAllResponse Object

Usage:

TimeSeriesClient\$.asGetAllResponse(jsonDict)

Arguments:

jsonDict JSON Response

Returns: DSUserObjectGetAllResponse object

Method .asGetResponse(): A helper method which converts the JSON response to GetResponse Object

Usage:

TimeSeriesClient\$.asGetResponse(jsonDict)

Arguments:

jsonDict JSON Response

Returns: DSUserObjectResponse object

Method .jsonRequestEncoder(): A helper method that reformats the raw request to JSON format

Usage:

TimeSeriesClient\$.jsonRequestEncoder(request)

Arguments:

request Raw request

Returns: return JSON formatted list

Method .jsonResponseDecoder(): A helper method that converts JSON Response to a given class response type

Usage:

TimeSeriesClient\$.jsonResponseDecoder(jsonResp, responseType)

Arguments:

jsonResp JSON Response

responseType GetResponse or GetAllResponse type

Returns: return DSUserObjectGetAllResponse or DSUserObjectGetResponse object

Method GetAllItems(): This method returns all the current timeseries you can use in Datas-
stream queries.

Usage:

```
TimeSeriesClient$GetAllItems()
```

Returns: DSUserObjectGetAllResponse object

Method GetItem(): GetItem returns the details for an individual timeseries.

Usage:

```
TimeSeriesClient$GetItem(itemId)
```

Arguments:

itemId : a valid timeseries Id.

Returns: DSUserObjectResponse object

Method CreateItem(): This method attempts to create the given DSTimeSeriesRequestObject
via the API service

Usage:

```
TimeSeriesClient$CreateItem(newItem, overWrite = FALSE, skipItemReturn = FALSE)
```

Arguments:

newItem A DSTimeSeriesRequestObject containing the data used for creating the Timeseries.

overWrite If the given Timeseries Id already exists on the system, the create call will be re-
jected. Set overWrite = True to overwrite the existing item with new Timeseries.

skipItemReturn : Upon successful creation of an item, the server requests the new item from
the mainframe and returns it in the response object. For faster processing, set skipItemRe-
turn = True to skip returning the object in the response

Returns: DSUserObjectResponse object

Method UpdateItem(): This method attempts to modify a timeseries item using the given
DSTimeSeriesRequestObject via the API service

Usage:

```
TimeSeriesClient$updateItem(item, skipItemReturn = FALSE)
```

Arguments:

item A DSTimeSeriesRequestObject containing the data used for creating the Timeseries.

skipItemReturn Upon successful creation of an item, the server requests the new item from the
mainframe and returns it in the response object. For faster processing, set skipItemReturn
= True to skip returning the object in the response.

Returns: DSUserObjectResponse object

Method DeleteItem(): DeleteItem allows you to delete an existing timeseries

Usage:

```
TimeSeriesClient$DeleteItem(itemId)
```

Arguments:

itemId a valid timeseries Id.

Returns: No return value

Method GetTimeseriesDateRange(): This method allows you to determine the supported dates between supplied start and end dates at a specified frequency.

Usage:

```
TimeSeriesClient$GetTimeseriesDateRange(
    startDate,
    endDate,
    frequency = DSUserObjectFrequency$Daily
)
```

Arguments:

startDate A date specifying the beginning of the date range

endDate A date specifying the end of the date range

frequency A DSUserObjectFrequency enumeration defining if the frequency should be daily, weekly, monthly, quarterly or yearly.

Returns: DSTimeSeriesDateRangeResponse object

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
TimeSeriesClient$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

: You need a Datastream ID which is permissioned to access the Datastream APIs. In addition, this ID also needs to be permissioned to access the custom user object service. Attempting to access this service without these permissions will result in a permission denied error response.

: For Daily and Weekly frequencies, if the supplied startDate falls on a weekend or a trading holiday, the returned starting date will be the first trading day before the given start date. If the supplied endDate falls on a weekend or a trading holiday, the returned final date will be the last trading day before the given end date. For Weekly frequencies, this will be the last date which matches the day of the week for the first returned start date.

For Monthly, Quarterly and Yearly frequencies, the returned dates are always the 1st day of each month, quarter or year. The returned start and end dates are always the 1st days of the requested month, quarter or year that the given start and end dates fall within.

: For Daily and Weekly frequencies, if the supplied startDate falls on a weekend or a trading holiday, the returned starting date will be the first trading day before the given start date. If the supplied endDate falls on a weekend or a trading holiday, the returned final date will be the last trading day before the given end date. For Weekly frequencies, this will be the last date which matches the day of the week for the first returned start date.

For Monthly, Quarterly and Yearly frequencies, the returned dates are always the 1st day of each month, quarter or year. The returned start and end dates are always the 1st days of the requested month, quarter or year that the given start and end dates fall within.

Examples

```

{
  # first logon with your credentials.
  # Creating a TimeSeriesClient instance with your credentials
  # automatically logs on for you.

  timeseriesClient = TimeSeriesClient$new(NULL, 'YourID', 'YourPwd')

  # query for all your current timeseries items

  itemsResp = timeseriesClient$GetAllItems()
  if (!is.null(itemsResp))
  {
    if (itemsResp$ResponseStatus != DSUserObjectResponseStatus$UserObjectSuccess)
    {
      # Your Datastream Id might not be permissioned for managing
      # user created items on this API

      print(paste('GetAllItems failed with error ',
        names(DSUserObjectResponseStatus)[[itemsResp$ResponseStatus + 1]],
        ': ', itemsResp$ErrorMessage))
    }
    else if (!is.null(itemsResp$UserObjects) & itemsResp$UserObjectsCount > 0)
    {
      # You do have access to some timeseries
      # Here we just put the timeseries details into a dataframe and list them
      print(paste('GetAllItems returned', itemsResp$UserObjectsCount, 'timeseries items.'))
      df = data.frame()

      for (tsItem in itemsResp$UserObjects)
      {
        if (!is.null(tsItem))
        {
          rowdata = list(Id = tsItem$Id,
            LastModified = tsItem$LastModified,
            StartDate = ifelse(!is.null(tsItem$DateInfo), as.character(tsItem$DateInfo$StartDate), ""),
            EndDate = ifelse(!is.null(tsItem$DateInfo), as.character(tsItem$DateInfo$EndDate), ""),
            Frequency = ifelse(!is.null(tsItem$DateInfo), tsItem$DateInfo$Frequency, 0),
            NoOfValues = ifelse(!is.null(tsItem$DateRange), tsItem$DateRange$ValuesCount, 0),
            Desc = tsItem$Description)
          df = rbind(df, rowdata)
        }
      }
      print(df)
    }
  }
  #Example to show how to GetItem
  # query for a specific timeseries

  tsName = 'TSZZZ001'
  tsResponse = timeseriesClient$GetItem(tsName)

```

```

# You may want to put the timeseries request response handling into a common function.
if (!is.null(tsResponse))
{
  # Any request dealing with a single user created item returns a DSUserObjectResponse.
  # This has ResponseStatus property that indicates success or failure

  if (tsResponse$ResponseStatus != DSUserObjectResponseStatus$UserObjectSuccess)
  {
    print(paste('Request failed for timeseries', tsName, 'with error',
              names(DSUserObjectResponseStatus)[[tsResponse$ResponseStatus+1]],
              ':', tsResponse$ErrorMessage))
  }
  else if (!is.null(tsResponse$UserObject))
  {
    # The timeseries item won't be returned if you set SkipItem true
    # in CreateItem or UpdateItem

    # Here we simply display the timeseries data using a dataframe.

    tsItem = tsResponse$UserObject
    metadata = c (Id = tsItem$Id,
                 Desc = tsItem$Description,
                 LastModified = as.character(tsItem$LastModified),
                 StartDate = ifelse (!is.null(tsItem$DateInfo), as.character(tsItem$DateInfo$StartDate), NULL),
                 EndDate = ifelse(!is.null(tsItem$DateInfo), as.character(tsItem$DateInfo$EndDate), NULL),
                 Frequency = ifelse(!is.null(tsItem$DateInfo),
                 names(DSUserObjectFrequency)[[tsItem$DateInfo$Frequency + 1]], NULL),
                 NoOfValues = ifelse(!is.null(tsItem$DateRange), tsItem$DateRange$ValuesCount , 0))

    df = data.frame(metadata)
    print(df)
    if (!is.null(tsItem$DateRange))
    {
      df = data.frame(Dates = sapply(tsItem$DateRange$Dates,
                                    FUN = function(x){ return (as.character(x)) } ),
                    Values = sapply(tsItem$DateRange$Values,
                                    FUN = function(x){ ifelse (is.null(x),
                                                                return (NA_character_ ), return (x) )} ))

      # Values if NULL, is printed as <NA> because, while
      # convertind list to vector either by using as.vector or sapply,
      # the NULL values in the list are deleted. and thus there will
      # be mismatch in no of rows and cannot be put in a dataframe

      print(df)
    }
  }
}
}
}

```

Index

* datasets

- DSTimeSeriesCarryIndicator, [9](#)
- DSTimeSeriesDateAlignment, [11](#)
- DSTimeSeriesFrequencyConversion, [15](#)
- DSUserObjectAccessRights, [20](#)
- DSUserObjectFrequency, [22](#)
- DSUserObjectResponseStatus, [25](#)
- DSUserObjectShareTypes, [25](#)
- DSUserObjectTypes, [26](#)

DataClient, [2](#)

DatastreamR::DSConnect, [3](#), [27](#)

DatastreamR::DSTimeSeriesUserObjectBase, [16](#), [17](#)

DatastreamR::DSUserObjectBase, [16](#), [17](#), [19](#)

DSConnect, [7](#)

DSTimeSeriesCarryIndicator, [9](#)

DSTimeSeriesDataInput, [10](#)

DSTimeSeriesDateAlignment, [11](#)

DSTimeSeriesDateInfo, [12](#)

DSTimeSeriesDateRange, [13](#)

DSTimeSeriesDateRangeResponse, [14](#)

DSTimeSeriesFrequencyConversion, [15](#)

DSTimeSeriesRequestObject, [16](#)

DSTimeSeriesResponseObject, [17](#)

DSTimeSeriesUserObjectBase, [18](#)

DSUserObjectAccessRights, [20](#)

DSUserObjectBase, [20](#)

DSUserObjectFrequency, [22](#)

DSUserObjectGetAllResponse, [22](#)

DSUserObjectResponse, [24](#)

DSUserObjectResponseStatus, [25](#)

DSUserObjectShareTypes, [25](#)

DSUserObjectTypes, [26](#)

TimeSeriesClient, [27](#)